



The Charcoal Plus 30 C tinted automotive window film confers a touch of aesthetic embellishment to any vehicle, whilst ensuring moderate privacy from prying eyes.

### Certifications



**Warranty SOLAR SCREEN®**  
See the 'New guarantees for outdoor products' notice



**Fire-Resistance Rating**  
M1



**Storage From -5°C To +40°C**  
3 years



**Reach Rohs Compliant**  
Respected



**Widths Available**  
152cm

### Construction

1. Dyed polyester without optical distortion
2. Bonding adhesive
3. Dyed polyester without optical distortion
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

### Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

### Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	67%
Reflection Of External Visible Light	6%
Reflection Of Internal Visible Light	5%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	8%
Solar Energy Absorption	33%
Solar Energy Transmission	59%
Reduction In Solar Glare	29%
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	55µ
Colour From The Outside	BLACK

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	!

✓ Yes ✗ Not Recommended ! Caution

These general recommendations are to be complemented by a commitment-free detailed thermal analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.