



The Classic decorative film allows you to effectively personalise your windows and glass partitions. It provides privacy thanks to its frosted aspect angel hair effect patterning.

Certifications



Warranty SOLAR SCREEN®
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	
Visible Light Transmission	
Reflection Of External Visible Light	
Reflection Of Internal Visible Light	
Total Solar Energy Rejected	
Total Solar Energy Rejected 2*	
Solar Ratio :	
Solar Energy Reflection	
Solar Energy Absorption	
Solar Energy Transmission	
Reduction In Solar Glare	
Shading Coefficient	
Installation Type	Interior
Roll Length	50 meters m
Film Composition	PET
Thickness	40µ
Colour From The Outside	WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.