

## CLEAR 18 C

Safetv Transparent burglary protection film



Clear 18 C films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Ideal for use on large glazed surfaces, these films are European Standard EN 356 compliant.

### Certifications

Warranty SOLAR SCREEN® See the 'New guarantees for outdoor products' notice

**Fire-Resistance Rating** 

Storage From -5°C To +40°C 3 years

**Reach Rohs Compliant** Respected

P2A

#### Widths Available

152cm

# 1. Hard scratch resistant layer, for

Construction

- durability and ease of maintenance during window cleaning
- 2. High optical quality polyester 150µ
- 3. Bonding adhesive
- 4. High optical quality polyester 150µ
- 5. Bonding adhesive
- 6. High optical quality polyester 150µ 7. Reinforced PS Adhesive to accompany
- the elasticity of the film in case of impact, glass polymerization within 30 days
- 8. Protection release liner, disposable after installation

### **Maintenance Instructions**

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

### **Technical Datasheet**

Ultraviolet Transmission	5%
Visible Light Transmission	80%
Reflection Of External Visible Light	12%
Reflection Of Internal Visible Light	12%
Total Solar Energy Rejected	20%
Total Solar Energy Rejected 2*	21%
Solar Ratio : Solar Energy Reflection	10%
Solar Energy Absorption	9%
Solar Energy Transmission	81%
Reduction In Solar Glare	16%
G-Value	0.8
U-Value	5.7
Shading Coefficient	0.9
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	520µ
Colour From The Outside	TRANSPARENT

### **Installation Advice**

Vertical position and standard glass surface\*

Clear Single Pane	~
Tinted Single Pane	~
Reflective Tinted Single Pane	~
Clear Double Pane	~
Tinted Double Pane	~
Reflective Tinted Double Pane	~
Gas-Filled Double Pane - Low E	~
Stadip Ext. Clear Double Pane	~
Stadip Int. Clear Double Pane	~

✓ Yes X Not Recommended Caution

\\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

SOLAR SCREEN® EUROPEAN SALES CENTER 18 Rue du Commerce L-3895 FOETZ TEL : +352 26 00 84 82 WWW.SOLARSCREEN.EU