









Clear 4 XC G solvent resistant films provide highly effective protection against tags and graffiti. Its protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion or serious impact.

### Certifications

-  **Warranty SOLAR SCREEN®**  
See the 'New guarantees for outdoor products' notice
-  **Fire-Resistance Rating**  
M1
-  **Storage From -5°C To +40°C**  
3 years
-  **Reach Rohs Compliant**  
Respected
-  **European Standard EN 12600**  
2B2
-  **Widths Available**  
122cm 152cm 183cm

### Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

### Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

### Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	93%
Reflection Of External Visible Light	9%
Reflection Of Internal Visible Light	9%
Total Solar Energy Rejected	17%
Total Solar Energy Rejected 2*	18%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	8%
Solar Energy Transmission	82%
Reduction In Solar Glare	14%
G-Value	0.83
U-Value	5.7
Shading Coefficient	0.9
Installation Type	Exterior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	125µ
Colour From The Outside	TRANSPARENT

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.