



Clear 8 XC films help secure your windows by ensuring that the glass does not shatter, remaining transparent and retaining its overall integrity in the event of an impact, explosion or fire. Comply with European Standard EN 12600.

Certifications



Warranty SOLAR SCREEN®
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



European Standard EN 12600
1B1



Widths Available
152cm 183cm

Construction

1. "Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Bonding adhesive
4. High optical quality polyester
5. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	83%
Reflection Of External Visible Light	10%
Reflection Of Internal Visible Light	10%
Total Solar Energy Rejected	20%
Total Solar Energy Rejected 2*	21%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	14%
Solar Energy Transmission	76%
Reduction In Solar Glare	15%
G-Value	0.82
U-Value	5.7
Shading Coefficient	0.9
Installation Type	Exterior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	240µ
Colour From The Outside	TRANSPARENT

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.