



Decorative film with white gradient from the center to the top and bottom, offering elegance, brightness and partial privacy.

## Certifications



### Warranty SOLAR SCREEN®

5 years  
See the 'New guarantees for outdoor products' notice



### Fire-Resistance Rating

M1



### Storage From -5°C To +40°C

3 years



### Reach Rohs Compliant

Respected



### Widths Available

152cm 210cm

## Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

## Maintenance Instructions

Soapy water solution (ref. Film On 600-F0355), do not clean before at least 1 month and do not apply any sticker or other adhesive on the film.

## Technical Datasheet

Installation Type	Interior
Roll Length	30.5m m
Film Composition	PET
Thickness	60µ
Colour From The Outside	WHITE

## Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

\*Advice based on glazed surface up to 2.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.