



Mat Acid privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. Printable on any type of machine.

Certifications



Warranty SOLAR SCREEN®
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. 80µ polymer PVC
2. Half permanent adhesive, allowing the degassing of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	>25%
Visible Light Transmission	45%
Reflection Of External Visible Light	20%
Reflection Of Internal Visible Light	20%
Total Solar Energy Rejected	30%
Total Solar Energy Rejected 2*	30%
Solar Ratio :	
Solar Energy Reflection	19%
Solar Energy Absorption	14%
Solar Energy Transmission	67%
Reduction In Solar Glare	56%
G-Value	0.71
U-Value	5.6
Installation Type	Interior
Roll Length	50 meters m
Film Composition	PVC
Thickness	80µ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.