



Thanks to this film carefully applied to your glazing, you can project any movies and/or image types for a perfect result.

Certifications



Warranty SOLAR SCREEN®

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. 25μ frosted polyester with satin surface
2. Bonding adhesive
3. Polyester 100μ
4. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	5%
Visible Light Transmission	71%
Reflection Of External Visible Light	26%
Reflection Of Internal Visible Light	26%
Total Solar Energy Rejected	28%
Total Solar Energy Rejected 2*	27%
Solar Ratio :	
Solar Energy Reflection	23%
Solar Energy Absorption	6%
Solar Energy Transmission	71%
Reduction In Solar Glare	22%
G-Value	0.71
U-Value	5.6
Shading Coefficient	0.8
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	150μ
Colour From The Outside	WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.