Safety Anti-Graffiti



Protec 6 C solvent resistant films provide highly effective protection against tags and graffiti. The film's protective qualities are not limited to solvents, it will also shield a window's surface from other acts of vandalism involving scratching or acid etching. An easy film to install and replace, it is also classed as a security film, providing protection by holding shattered glass in place in the event of an explosion, impact or fire.

Certifications



Warranty SOLAR SCREEN® See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available

Construction

- Hard" scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. High optical quality polyester
- Half permanent adhesive that will ease the removal of the film from the window
- 4. Protection release liner, disposable after installation

Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Technical Datasheet

Ultraviolet Transmission	5%
Visible Light Transmission	86%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	20%
Total Solar Energy Rejected 2*	20%
Solar Ratio : Solar Energy Reflection	10%
Solar Energy Absorption	8%
Solar Energy Transmission	83%
Reduction In Solar Glare	14%
G-Value	0.83
U-Value	5.7
Shading Coefficient	0.9
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	180μ
Colour From The Outside	TRANSPARENT

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane

Tinted Single Pane

Reflective Tinted Single Pane

Clear Double Pane

Tinted Double Pane

Reflective Tinted Double Pane

Gas-Filled Double Pane - Low E

Stadip Ext. Clear Double Pane

√ Yes

X Not Recommended

Caution

Cautio

Stadip Int. Clear Double Pane

*Recommendations provided on the basis of a glazed surface covering up to $2.5 \, \text{m}^2$.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.