



### Certifications



**Warranty SOLAR SCREEN®**

See the 'New guarantees for outdoor products' notice



**Fire-Resistance Rating**



**Storage From -5°C To +40°C**



**Reach Rohs Compliant**

Respected



**Widths Available**

51cm 122cm 152cm 76cm 92cm  
101cm 135cm 136cm 137cm  
140cm 182cm 183cm

### Construction

1. High optical quality polyester
2. Bonding adhesive
3. PVC with anti IR metal particles deposit
4. Protection liner, disposable after installation

### Maintenance Instructions

### Technical Datasheet

Solar Ratio :

Solar Energy Reflection

Solar Energy Absorption

Solar Energy Transmission

Installation Type

Exterior

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane



Tinted Single Pane



Reflective Tinted Single Pane



Clear Double Pane



Tinted Double Pane



Reflective Tinted Double Pane



Gas-Filled Double Pane - Low E



Stadip Ext. Clear Double Pane



Stadip Int. Clear Double Pane



✓ Yes ✗ Not Recommended ! Caution

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.