



Decorative film with a white gradient from the bottom to the top, providing brightness and partial privacy with an elegant and modern style.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm 210cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. Film On 600-F0355), do not clean before at least 1 month and do not apply any sticker or other adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	
Reflection Of Internal Visible Light	
Solar Ratio :	
Solar Energy Absorption	
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5m m
Film Composition	PET
Thickness	60μ
Colour From The Outside	WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Advice based on glazed surface up to 2.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.